



Bars / Ice Cream / Small Grocery



## High Performance Fanless POS Touch Screen Terminal



Convenience Stores



Pizza / Table Service / Quick Service / Liquor Stores

## Powered With Intel Atom Dual-Core Processor to Run More Demanding Applications

The high performance SAM4S SPT-4700 touch screen terminal with a **dual-core fanless** CPU is designed to reliably and efficiently power demanding POS software applications in hospitality, quick service, grocery, and retail markets.

- 15" LCD with ELO® 5-Wire Resistive Touch
- Intel® Atom™ Dual Core 1.86GHz Fanless Processor
- **2GB RAM** Standard; Expandable to 4GB
- Compatible with Popular Application Software
- Easily Wall Mountable
- Variety of Optional Integrated Customer Displays
- Excellent Cable Management



Cafeterias / Delis



# SPT-4700 Touch Screen Terminal



**Optional Integrated 15" Rear LCD Customer Display**



**Optional Integrated 7" Rear LCD Customer Display**



**Optional Integrated VFD Customer Display**



**Tool-Free Access to Hard Disk Drive and RAM Optimizes Serviceability**

## Options and Upgrades

Configure your system with these easy to add options:

- Integrated VFD Customer Display – 2 Lines x 20 Characters
- Integrated 15" or 7" LCD Customer Displays
- Integrated Triple Track Card Reader with Integrated Fingerprint Reader
- CFast Slot / CFast Disk
- WiFi Module
- Wall Mount Bracket with Standard VESA Configuration

## Applications

The attractive, powerful SPT-4700 fanless terminal is ideal for harsh environments like pizza, quick service restaurants, bakeries and industrial shop floors and for processor intensive applications including table service, retail scanning and many more:


- Airline Counters
- Automotive Services
- Convenience Stores
- Digital Signage
- Dry Cleaners
- Financial/Banking
- Food & Drug Stores
- Gaming
- Hospitality
- Hotel Front Desk
- Interactive Workstations
- Kiosks
- Kitchen Video
- Medical
- Message Stations
- Point of Sale
- Quick Service Restaurant
- Rental Car
- Rental Stores
- Retail Scanning
- Self Service
- Streaming Video
- Table Service Restaurant
- Training
- Unattended Workstations

## Connectivity

- A** Drawer Voltage Selector Switch
- B** Cash Drawer
- C** Parallel
- D** Line-Out
- E** Mic-In
- F** Line-In
- G** USB (2)
- H** LAN
- I** COM1 (Powered)
- J** COM2 (Powered)
- K** USB (2)
- L** COM3 (Powered)
- M** VGA
- N** COM4 (Powered)
- O** DC Out (For Rear LCD)
- P** DC In (Power)

## Specifications

<b>Processor:</b>	Intel Atom D2550 1.86GHz (Cedarview) + NM10
<b>FSB (Front Side Bus):</b>	1333 MHz
<b>Socket Type:</b>	BGA
<b>Display LCD:</b>	15" LCD
<b>Resolution:</b>	1024 x 768
<b>Brightness:</b>	Adjustable Up to 250 cd/m2
<b>Integrated Speakers:</b>	Integrated 2 Watt Speakers
<b>Chipset:</b>	ICH8M
<b>Touch Panel:</b>	ELO 5-Wire Resistive Touch
<b>MCR:</b>	Integrated Triple Track MCR with Optional Encryption
<b>Hard Drive:</b>	2.5" With SATA Interface
<b>RAM Memory:</b>	2GB DDR3 800 SODIMM Expandable To 4GB (2 Slots)
<b>Video Memory:</b>	Shared Memory Up To 256MB For Primary LCD
<b>CFast Memory:</b>	Optional CFast Memory Card Slot
<b>Mini-PCle:</b>	Not Applicable
<b>Serial Ports – 4 External:</b>	<b>COM1, COM2, COM4</b> = DB9M With Pin 9 Voltage (0V/+5V/+12V) Selectable By BIOS / <b>COM3</b> = RJ45 Pin 1 Voltage (0V/+5V/+12V) Selectable By Jumper
<b>2 Internal:</b>	<b>COM5</b> = RJ45 for VFD / <b>COM6</b> for Primary Touchscreen
<b>Parallel Port:</b>	One DB25F
<b>USB Ports:</b>	6 V2.0 (2 Left Side / 4 Bottom)
<b>Cash Drawer Port:</b>	RJ11, 12V DC or 24V DC Selectable By Switch (Maximum 2 Drawers – Supports Open/Close)
<b>Keyboard / Mouse Port:</b>	Not Applicable (Use USB Ports)
<b>LAN Port:</b>	RJ45 10/100/1000 Base-T (Giga LAN) RealTek RTL8111DL
<b>VGA Port:</b>	One DB15F Display Port For Second LCD (Maximum Resolution 2048 x 1536)
<b>Audio Port:</b>	One Line-In / One Line-Out
<b>Mic Port:</b>	One Mic-In
<b>Power Supply:</b>	60W, 12V/5A External Power Adaptor 100-240V 50-60Hz
<b>Current / Power Usage:</b>	0.37A / 45W
<b>Operating Temperature:</b>	32° F to 95° F (0° C to 35° C)
<b>Compatible O/S:</b>	POSReady 2009 / XP-PRO Embedded / POSReady 7 / Winows 7 / Windows 8 (Available Soon)
<b>Dimensions – Base:</b>	11"W x 7-3/8"H x 8-5/8"D
<b>Overall:</b>	13-13/16"W x 12-1/8"H x 8-5/8"D
<b>Shipping Carton:</b>	20-1/4"W x 13"H x 16"D
<b>Weight – Product:</b>	12.9 lbs.
<b>Shipping:</b>	17.5 lbs.
<b>Safety and EMI:</b>	FCC, RoHS



All product and company names are trademarks, service marks or registered trademarks of their respective owners. All features and specifications are subject to change without notice.

© 2013, Printed in U.S.A.

Lit-219a

**SAM4S**